
Alimak FC 7100-12

Model 650 FC 32/39 Single Car Construction Hoist



SPECIFICATIONS

Meets the Requirements of ANSI A10.4

GENERAL

Max. load capacity[1] ..... 7,100 lbs
Max. freestanding mast height[2] ..... 30'-0"
Max. untied mast overhang[3] ..... 30'-0"
Max. mast tie spacing[3] ..... 30'-0"
Minimum mast tie spacing[3] ..... 19'-8"
Max. standard lifting height[4] ..... 660'
Number of passengers 29
Car inside dimensions (approx.) ..... 12'-9" x 4'-11" x 7'-6 1/2"
Side gate opening (if equipped) ..... 6'-6 3/4" x 10'-6"
Mast section length ..... 4'-11 3/8"
Speed ..... Up to 175 fpm

[1] Maximum capacity of 7,100 lbs to a lifting height of 300'. Contact Morrow Equipment for specific capacities at greater lifting heights.
[2] Requires use of an embedded foundation frame in lieu of mast anchor expansion bolts. See operation manual or contact Morrow engineering for specific information. Foundation anchorage provided by customer.
[3] Maximum untied mast overhang and mast tie spacing dimensions vary subject to installation conditions, manufacturer specifications, and regulatory compliance. See manufacturer data or contact Morrow Equipment for specific information.
[4] Greater lifting heights are available. Contact Morrow Equipment for specific information.

WEIGHTS

Base enclosure (without car) ..... 2,358 lbs
Base enclosure (with car) ..... 5,640 lbs
Motorpack (3 x 14.7 hp) ..... 1,965 lbs
Hoist car (without motorpack) ..... 3,282 lbs
Mast section (single rack) ..... 254 lbs

ELECTRIC POWER

480 V phase–phase, 277 V each phase to ground with 120° phase shift between phases. 3-phase, 60 Hz power supply plus ground wire. Do not use Open-Delta supply.

Motors (VFD) ..... 3 x 14.7 hp (11 kW)
Power supply fuses ..... 100 Amps
Starting current ..... 91 Amps
Power consumption ..... 66 kVA

@MorrowEquipment:
(503) 585-5721
info@morrow.com
morrow.com